

PRODUCT FICHE FOR UPRIGHT REFRIGERATED CABINETS OF MODEL

SCh-Z/1600/W ecoline

Trade mark RA TAPA

Model SCh-Z/1600/W ecoline

Appliance storage

Refrigeration working temperature $-1^{\circ}\text{C} \div +7^{\circ}\text{C}$

Category upright

Refrigerant R-290 (ODP = 0; GWP = 3)

Upright refrigerated cabinet of light-

lutv

This appliance is intended for use in ambient temperatures up to 25 $^{\circ}\text{C}$ and therefore is not suitable for use in hot professional kitchens.

Optimization and recommendations of device usage

In order to reach the parameters related to the energy efficiency given in the below table it is necessary to follow the instructions in the user manual.

Parametr	Symbol	Value	Unit of measure
Energy efficiency class	_	D	_
Annual energy consumption	AEC	1419	kWh
Energy efficiency index*	EEI	73,60	_
Net volume	Vn	802,20	1
Test room climate class		3	_
Amount of refrigerant	R-290	0,15	kg
Contact details	RAPA S. Międlar W. i I. Szymańscy sp. j.		

^{9,} Ceramiczna Street 20-149 Lublin POLAND

^{* -} for goods temperature up to +5°C (accordingly to the regulation (EU) 2015/1094 supplementing Directive 2010/30/EU of the European Parliament)