





Refrigerated confectionary display case **C-A**

Net catalog p	rices	
display case	A 102:	1 951 EUR
display case	A 139:	2 018 EUR

Dimension [cm]

Confectionery display case	A 102	A 139
length	102	139
depth	89	89
height	146	146
exposition dimensions	38x93 - 3 pcs.	38x130 - 3 pcs.
bottom exposition	51x93	51x93
shelves spacing	1x17; 2x19; 1x25	1x17; 2x19; 1x25

Parameters

temperatures range	+4°C÷+10°C	
refrigerant (HFC)	R-452A	
rated voltage	230 V~/ 50 Hz	
power rating	980 W (A 102) 1030 W (A139)	
defrosting	automatic	
evaporation of condensate	automatic	

Colours



* All prices are calculated accordingly to the hereby exchange rate 1 EUR = 4,3 PLN. The exact prices on the invoice will be calculated due to average exchange rate announced as valid ones by The Polish National Bank one day before the date of commercial / proforma invoice issuance.

1

+48 81 742 53 10 rapa@rapa.lublin.pl www.rapa.pl



Device characteristics Refrigerated confectionary display case C-A

Standard equipment

Refrigerating unit

- 3rd climatic class
- Plug-in unit powered with ecological R-290 refrigerant
- Fan assisted cooling (dynamic)
- Electronic temperature controller with display from the service side(setting range: +3°C ÷ +18°C)
- Pollen filter
- Air curtain eliminating losses when opening the door
- Automatic condensate evaporation system
- Glass panes drainage system

Housing

- Vent lockable with magnet
- Glass panes demountable without using tools: sides, top and shelves (apart from the door and front glass pane)
- Glass cover isolating the glass top of the device
- Adjustable legs
- Backlighted bottom of the device
- Cover made of furniture board decor to be chosen from the RAPA pattern

Exposition

- Additional glass worktop inside
- Sliding door made of combined, low-E glass panes
- LED lighting of each shelf and worktop
- Front glass pane flat, vertical, tilted with wire tensioner
- External glass panes, worktop and shelves tempered

Additional equipment

- - Decor different than from the RAPA pattern
- Double electric socket
- Device without aggregate
- Built-in device (without sides and panels)

Accessories



USB temperature recorder - wireless

2